









Recreational Water Systems • White Bear Lake, MN • 612-325-2886 • SoftCell@comcast.net
SoftCellWater.com

Attached Pre-Filter Assembly Instructions

For best results and years of trouble free service we recommend the use of a PRE-FILTER










1		<p>Remove clear bottom from Pre-Filter housing cap. Remove any paper on filter cartridge</p>	4		<p>Replace clear housing bottom, hand tighten</p>
2		<p>Screw black housing cap unto brass pipe connector <u>"Caution" be careful not to cross thread cap</u></p>	5		<p>Connect supplied 48" hose to Pre-Filter housing</p>
3		<p>Hand tighten black cap</p>	6		<p>Connect 48" hose to a water supply and attach your hose to the discharge side of the SoftCell, check for leaks and tighten any fittings as needed</p>

Before first use run water through softener. The water may run tea colored because of the indentifier dye on the softening resin. Run water until water runs clear.

Your SoftCell softener is now ready for regular use. The hardness of your water will determine how often regeneration will be required. The softener should be regenerated when you do not feel the slippery feeling of soft water or you start to see water spotting. (See Reverse Side)

If you have any questions do not hesitate to call at 612-325-2886

Attached Pre-Filter Re-generation Instructions

1		Remove sediment cartridge from the Pre-Filter Housing
6		The salt will dissolve slowly as the water runs through the Pre-Filter regenerating the softener
2		Fill bottom of Pre-Filter housing with "MORTON" water softener salt pellets
7		When the salt has dissolved and there is no salt taste in the water being discharged, pivot the Pre-Filter back down
3		Re-attach Pre-Filter bottom
8		Remove bottom, rinse out any residue, and replace with new sediment cartridge if the old one is dirty
4		Tighten and start to run water at the slow rate of 1/2 gallon per minute (a pencil size stream)
9		Attach your hose to the discharge side of the SoftCell, check for leaks and tighten any fittings as needed
5		Pivot Pre-Filter housing upside down (This shortens the regeneration time)

Long Term Storage and Winterization

- Remove all hoses
 - Remove cartridge from Pre-Filter housing
 - Invert softener and empty out all water
- ### Re-Commissioning
- Connect and run water for a few minutes until water runs clear

Note:

The Pre-Filter housing uses a standard 10", 10 or 20 micron sediment cartridge available at most big box home stores. We recommend using "Morton" home water softener salt as it dissolves faster and leaves little residue.